

MAX 50 le MICROFORST rc

Radio Controlled Carrier with Forestry Mulcher







MAX 50 le & MICROFORST rc

Radio controlled carrier with forestry mulcher

The **MAX 50 le** radio controlled vehicle is built extra strong to handle the most extreme and demanding jobs. With 49 hp, the vehicle offers maximum reliability thanks to the industrial 3-cylinder turbo diesel engine T4F/STAGE V from Perkins. Vehicle stability and traction are guaranteed even in difficult terrain thanks to the optimally positioned center of gravity. The track width can be extended up to 181 cm [71"]and can thus manage slopes up to 55° of incline. The generous hydraulic power promises the necessary torque to master even the most difficult situations.

MAX 50 le Self-propelled machinery

- Lifting linkage with assisted floating FLOAT
- > Chassis with roll-bar
- Internal components protected by steel hoods
- Underbody protections protects the motor and hydraulics
- > Hydraulic adjustment of the vehicle width 500 mm (2x250 mm) [20 inch = 2x10 inch]
- > Active AUTO TRACK TENSION system
- > Stability and traction due to superior track profile with high ground contact and LGP undercarriage. HIGH GRIP
- > Automatic reversible fan
- Remote control with display (Vital machine diagnostics and incline display)
 2.4 Ghz - 160 m range
- > 3 Cylinder T4F/STAGE V Perkins engine 1660 cc
- 2 auxiliary double acting hydraulic functions
- Closed circuit tandem piston pump with variable displacement

MICROFORST rc 125 Forestry mulcher


- > Mulches wood up to 15 cm [5.9"] Ø
- > Chassis made of
- wear-resistant steel AR400
- > Belt transmission
- > 30 cc PISTON MOTOR with flushing valve
- > Hydraulically operated hood
- > Guard frame
- Reinforced support skids, adjustable in height
- Helical rotor with fixed hammers of choice MINI DUO CARBIDE inserts hammers or MINI BLADE with CUT CONTROL gauge

le = linear extension rc = radio controlled



YouTube www.youtube.com/seppimulcher

Specifications	MAX 50 le	MICROFORST rc		
Rotor working width	-	125 cm [49"]		
Overall width	131-181 cm [52-71"]	144 cm [57"]		
Depth	215 cm [85"]	86 cm [34"]		
Height	119 cm [47"]	76 cm [30"]		
Weight	1.400 kg [3.090 lb]	330 kg [730 lb]		
Fixed hammers	-	27		



The information in this document is intended as a guide only. SEPPI M. may change their products or their specifications at any time without any obligation of previous notice.

Power & high-performance hydraulic drive

МАХ	50 le	DIESEL FUEL TANK	HYDRAULIC Fluid Tank	MULCHER HYDRAULICS		TRACKS HYDRAULICS		SECONDARY HYDRAULICS	
HP [kW]	l/min [gpm]	l [gallon]	l [gallon]	bar [psi]	l/min [gpm]	bar [psi]	l/min [gpm]	bar [psi]	l/min [gpm]
49 [36]	15 [4]	29 [7.5]	50 [13]	320 [4,640]	80 [21]	320 [4,640]	104 [27]	200 [2,900]	15 [4]



Extendable undercarriage for extending the width of the individual tracks. Powerful both when climbing slopes and when crossing extreme slopes. With the enlarged undercarriage, the mulcher works more efficiently and precisely on extreme and uneven grades..

FLOAT

Lifting linkage with assisted floating



A special feature is the radio control, which is equipped with a graphic display that monitors all functions and interference. The frequency range is 2.4 GHz and covers distances up to 160 m.






Standard rotor: MINI DUO hammer 2 tungsten carbide tips provide high performance and long lifetime > Efficient on big wood and stumps



Optional rotor: CUT CONTROL system The sharpenable blade of the MINI BLADE tool with the specially developed gauge reduces the depth of cut > Fast cut and fine mulch on wood and standing trees



Stability and grip of the vehicle on difficult terrain up to 55° slopes under optimal conditions













SHEEL ON SHO AND 14 Res











SEPPI M. SpA Italy Via Trento, 111 I-38017 Mezzolombardo (TN) T. +39 0461 178 75 00

RI 🖪 😁

SEPPI M. USA Division of SEPPI M. SpA 9077 Gold Park Drive West Chester, OH 45011 T. +1 513 443 6339

